



Portable Autoclave LD-LPOA-B15

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Portable Autoclave LD-LPOA-B15

Overview

Portable autoclave LPOA-B15 is an 18 L top loading microprocessor controlled automatic autoclave with a sterilizing temperature of 126 °C. The lid is a hand wheel, making it easy to use than the conventional knobs. Self-inflating leak proof chamber provides efficient sterilization. Equipped with safety features like automatic shutoff preventing overload of current, auto protection against raised temperature and pressure making a reliable and user friendly device.

Features:

- Working temperature : 126 ?
- Overheating and pressure warning indicator
- Digital display to monitor working status and parameters
- Indicator light to indicate the working
- Automatic beep indication at the end of every cycle
- Automatic power cut off with alarm with low water levels indication
- Self-inflating leak proof chamber
- Dual scale indicating pressure gauge
- Electric heated

Applications:

Used in industries to sterilize equipment, bacteriological and research laboratories, medical, clinical and pharmaceutical industries

Specifications:

Power	AC 220 V / 50 Hz
Net Weight	12 Kg
Gross Weight	14 Kg
Heat average	? ± 1?
Heating mode	Electrically heated
Temp adjustment	105 ~ 126 ?
Working pressure	0.14 ~ 0.16 MPa
Overall Dimension	420 × 420 × 630 mm
Volume of Chamber	18 L
Max safety pressure	0.165 MPa
Working temperature	126 ?