



Portable Chlorophyll Meter LD-LCPM-A10

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Portable Chlorophyll Meter LD-LCPM-A10

Overview

Chlorophyll Meter LD-LCPM-A10 is a handheld meter that offers 0.0 to 99.9 SPAD and -10 to 99.9°C measuring range to assess the chlorophyll concentration in plant leaves. Supplied with 2 LED light sources i.e., red light (650 nm) and infrared light (940 nm) for perfect inspection. Designed with LCD screen, that provides real-time data display with 2×2 mm of measuring area. It can directly measure chlorophyll and nitrogen concentration in the leaf without plucking it.

Features:

- A compact and portable microprocessor comprised of unit
- 2-wavelength concentration difference of optical measuring methods
- Silicon semiconductor photodiode sensor, for quick and non-destructive detection
- Testing parameters for plant's nitrogen, chlorophyll, leaf structure, and leaf humidity
- Imported with a rechargeable Li-battery allows long and worry-free operation
- 30 KB memory with USB interface, for convenient data processing and storage
- Configured with a memory card that allows data storage capacity of 999 groups, for the management and analysis
- Software program with online upgrade and data visualization via chart or curve
- Automatic calculation of average, reduced operation time
- An optimal unit to measure the relative amount of chlorophyll present in plant leaves

Applications:

Chlorophyll meter is used to measure chlorophyll content of plants or greenness, leaf temperature, to increase the utilization of nitrogen fertilizer across agriculture, plant biotechnology etc.

Specifications:

Power	4.2V -2000Mah rechargeable Li battery
Memory	30 KB
Sensor	Silicon semiconductor photodiode sensor
Weight	200 gm
Display	LCD
Controller	Microprocessor
Display mode	3 digits measuring value and 2 digits measuring times
Measuring Mode	2-wavelength concentration difference of optical methods
Measuring area	2×2 mm

Measuring range	0.0 to 99.9 SPAD and -10 to 99.9°C
Measuring accuracy	± 3 SPAD, ± 0.5°C
Operating Temperature	-10 to 50°C
Measuring repeatability	± 0.3 SPAD, ± 0.2°C
Minimum Measuring Interval	< 3 s