



-5/-30°C Upright Freezers LD-LUF-F13

Labodam Equipment Ltd.
info@labodam.com | www.labodam.com

-5/-30°C Upright Freezers LD-LUF-F13

Overview

-5/-30 °C Upright Freezer LD-LUF-F13 is microprocessor controlled unit, comes with 677 L capacity with temperature range of -5 to -30°C. Features forced cooling with automatic defrost system and CFC free refrigerant. The external material of the freezer is made of galvanized steel treated with electrostatic paint for protection against rust and inner surface is made of stainless steel. Freezer comes with 4 wire shelves. Equipped with digital display and advanced alarm system with turn-on delay and stopping interval protection function, has keyboard lock function to prevent unauthorized access.

Features:

- A microprocessor controlled upright type unit with 677 L of capacity
- Temperature range is -5/30 °C with forced cooling
- CFC free refrigerant with automatic defrost energy efficient and environment friendly
- External material is made up of galvanized steel and inner material is made up of stainless steel
- Insulated with high density polyurethane material
- Negative Temperature Coefficient temperature sensor ensure high-precision temperature control
- Digital display and advanced alarm system, ensures safe and secure storage
- Password protection system to prevent unauthorized access
- Stores data of 30 days in its memory
- The device features a USB output. The user can utilize a USB device to store cabinet degrees on an external flash memory for ten years, and then transfer the excel-formatted data to a PC

Applications:

-5/30°C Upright freezer is used for scientific research, cryogenic test on special materials, blood plasma cryopreservation, low temperature resistance test on biological materials, vaccines, biological products and military products, etc. across research institutions, the electronic industry, the chemical industry, hospitals, the health & disease prevention system, laboratories in colleges & universities, military enterprises, etc.

Specifications:

Weight	260 kg
Casters	2+2 levelling feet
Display	Digital
Shelves	4 pcs wired shelves
Capacity	677 L
Compressor	1 pc
Controller	Microprocessor
Refrigerant	R404a

Alarm System	High/Low temperature, Sensor failure, Door Ajar
Cabinet Type	Upright
Defrost Mode	Automatic
Power Supply	220 to 240 V/50 Hz
Cooling Method	Forced Cooling
Thermal Printer	Optional
External Material	Epoxy coated Stainless Steel Material
Internal Material	Stainless Steel Material
Temperature Range	-5/-30°C
Door lock with Key	Yes
Cooling Performance	-30°C
Insulation thickness	78.5 mm
External Dimension (WxDxH)	910 x 842 x 1938 mm
Internal Dimension (WxDxH)	753 x 630 x 1427 mm
Packaging Dimension (WxDxH)	990 x 980 x 2100 mm