



## **Multi-Position Heating Mantle LD-LMHM- A11**

**Labodam Equipment Ltd.**  
**[info@labodam.com](mailto:info@labodam.com) | [www.labodam.com](http://www.labodam.com)**

# Multi-Position Heating Mantle LD-LMHM-A11

## Overview

Multi-Position Heating Mantle LD-LMHM-A11 is a table top device with 6 × 250 ml maximum capacity, offers 6 channel multi-position heating mantle and temperature ranges from RT+20 to 250°C. It offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability. Features anti-corrosion, age-resistant and rotatory knob for setting of temperature and speed on hot plate. It adopts electronic temperature regulation heating mode.

## Features:

- Designed with electronic temperature regulation heating mode
- Rotatory knob to set temperature and speed
- Offers 6 channel multi-position heating mantle
- The maximum temperature is up to 450°C
- Equipped with cold rolling sheet stretching and spraying exterior
- Offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability
- Equipped by anti-corrosion, age-resistant, durable and safe
- The stirrer is operated synchronously to provide the same reaction conditions as the sample
- Effectively reduce the speed noise

## Applications:

Multi-Position Heating Mantle is used in petrochemical industries, medicine, and environment protection institutions for liquid heating, chemical synthesis, physical and chemical analysis, biopharmaceuticals etc.

## Specifications:

<b>Capacity</b>	6 × 250 ml
<b>Net weight</b>	15 kg
<b>Work model</b>	Continuous
<b>Outer shell</b>	Cold rolled steel plate, surface spraying
<b>Gross weight</b>	17 kg
<b>Heating mode</b>	Surface heat conduction
<b>Power supply</b>	200 to 240 V
<b>Heating Power</b>	6 × 0.15 kW
<b>Heating element</b>	Nickel chromium alloy wire
<b>Packing dimension</b>	980 × 190 × 200 mm
<b>Temperature range</b>	RT+20 to 250°C

<b>External dimension</b>	940 × 160 × 170 mm
<b>Surface Max. temperature</b>	450°C