



## **Multi-Position Heating Mantle LD-LMHM-A23**

**Labodam Equipment Ltd.**  
**[info@labodam.com](mailto:info@labodam.com) | [www.labodam.com](http://www.labodam.com)**

# Multi-Position Heating Mantle LD-LMHM-A23

## Overview

Multi-Position Heating Mantle LD-LMHM-A23 is a table top device with 4 × 1000 ml maximum capacity, offers 4 channel multi-position heating mantle and temperature ranges from RT+20 to 250°C. It offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability. Features anti-corrosion, age-resistant and rotatory knob for setting of temperature and speed on hot plate. It adopts electronic temperature regulation heating mode.

## Features:

- Designed with electronic temperature regulation heating mode
- Rotatory knob to set temperature and speed
- Offers 6 channel multi-position heating mantle
- The maximum temperature is up to 450°C
- Equipped with cold rolling sheet stretching and spraying exterior
- Offers step less speed adjustment, uniform temperature, fast heating-up, safety and durability
- Equipped by anti-corrosion, age-resistant, durable and safe
- The stirrer is operated synchronously to provide the same reaction conditions as the sample
- Effectively reduce the speed noise

## Applications:

Multi-Position Heating Mantle is used in petrochemical industries, medicine, and environment protection institutions for liquid heating, chemical synthesis, physical and chemical analysis, biopharmaceuticals etc.

## Specifications:

<b>Capacity</b>	4 × 1000 ml
<b>Net weight</b>	14 kg
<b>Work model</b>	Continuous
<b>Outer shell</b>	Cold rolled steel plate, surface spraying
<b>Gross weight</b>	16 kg
<b>Heating mode</b>	Surface heat conduction
<b>Power supply</b>	200 to 240 V
<b>Heating Power</b>	4 × 0.35 kW
<b>Heating element</b>	Nickel chromium alloy wire
<b>Packing dimension</b>	850 × 250 × 230 mm
<b>Temperature range</b>	RT+20 to 250°C

<b>External dimension</b>	810 × 210 × 200 mm
<b>Surface Max. temperature</b>	450°C