



Type I and Type III RO Water Purification System LD-LOTW-A14

Labodam Equipment Ltd.
info@labodam.com | www.labodam.com

Type I and Type III RO Water Purification System LD-LOTW-A14

Overview

Type I and Type III RO Water Purification System LOTW-A14 is an ideal purifier for users who require constant production of Type I and Type III water. It is incorporated with advanced systems like RO and electrodeionization which helps user in controlling the water quality. This combinational system produces Type III water after RO and Type I water after deionization in one cycle. Users can extract Type III water from the tank or Type I water from the dispenser with the help of 2 integrated outlets. It's designed to deliver compliant purified water with clear quality parameters and care free maintenance

Features:

- Advanced Single Pass reverse osmosis system for excellent water quality
- One step purification from tap water to Type I and Type III water
- Equipped with 80 L water holding tank
- Least TOC level < 3 ppb
- Source of inlet water " Tap water
- Equipped with 2 outlets for Type I and Type III water
- Floor Standing model
- LCD display to display the intake of water pressure and various parameters intuitively
- Programmed water shortage protection alarm
- Anti-fouling RO membrane prevention programme
- Online monitoring of water resistance
- Ease of cleansing , disinfecting and draining waste water
- Micro filter membrane to filter out pollutants
- Automatic RO membrane antiscaling flushing to extend the life of the RO membrane

Specifications:

TOC	< 20 ppb
Power	? 200 W
Weight	30 kg
Process	Single Pass RO system
Pyrogens	< 0.02 EU / ml
Water Type	Type I and Type III
Heavy metal	< 0.01 ppm
Configuration	Floor Standing
Water Tank capacity	80 L
Output of Pure water	? 50 L / hr.

Absorbance (254 nm)	? 0.001
Resistivity at 25 °C	18.25 M ?. cm
Conductivity at 25 °C	? 10 µs / cm
Electrical requirements	220 V / 50 Hz
Dimensions (L x W x H)	340 x 550 x 530 mm
Reactive Silica (SiO₂)	< 0.01 ppm
Output of Ultrapure water	? 1- 1.5 L / min