låbodam



Power Adjustable Ultrasonic Cleaner LPAU-A13

Power Adjustable Ultrasonic Cleaner LPAU-A13

Power Adjustable Ultrasonic Cleaner LPAU-A13 is the most reliable instrument with 22 L of tank capacity with a cleaning duration of 1 ~ 99 mins for efficient intensive cleaning of instruments and products making them contamination, rust and germ free. Its key feature is the variance of using it at 28 KHz for gross rinse to 40 KHz for intensive rinse. The power can be adjusted which provides the user with a precise control from zero watts to maximum power.

Features

- 22 L capacity tank
- ♦ Temperature range : 0 °C ~ 80 °C
- Cleaning duration: 1 ~ 99 mins
- 28 KHz for gross rinse to 40 KHz for intensive rinse
- One key access for auto stand-by, sleep and wake up mode
- Integrated digital circuit for timer and heater
- Precise digital processed temperature controls
- Efficient cleaning by distilled water
- Optimum durability under prolonged and heavy usage
- Equipped with degassing and degreasing function

Application

Ideal for cleaning irregular and complex instruments, lenses and other optical parts, dental and surgical instruments, electronics. It is also used in extraction and to degas certain analyzed stuff in laboratories

Power Adjustable Ultrasonic Cleaner LPAU-A13

Specifications

| Model No. | LPAU - A13 |
|------------------------------|--------------------|
| Capacity | 22 L |
| Tank size (L x W x H) | 500 x 300 x 150 mm |
| Overall size (L x W x H) | 550 x 330 x 337 mm |
| Ultrasonic power | O ~ 480 W |
| Heater power | 500 W |
| Temperature set | 0 °C ~ 80 °C |
| Digital timer (mechanical) | 1 ~ 99 mins |
| Construction material | Stainless Steel |
| Drainage | Yes |
| Voltage | AC 220 V / 50 Hz |