läbodam



Freezers

-65°C Ultra Low Temperature Upright Freezers

-65°C Ultra Low Temperature Upright Freezers LUF-C2 Series

These -65°C ultra low temperature freezers are designed with four casters for easy handling and vacuum release port to allow easy access to the sample after opening of the door and lockable door to prevent unauthorized access. Freezers are equipped with audio and visual alarm for power failure and system failure. The -65°C ultra low temperature upright freezers are complied with CE, ISO9001, ISO14001, ISO13485 standards and powerful system to keep the stored products frozen and preserved for a long duration. Ultra low temperature upright freezers comes with wide range of capacity from 100L to 828L.

Features

- Microprocessor-based temperature controller with digital temperature display allow user to maintain temperature between -10°C to -65°C with 1°C precision control
- Key board lock and password protected configuration page is installed with delayed start and safe stop interval between restart and being terminated
- For hazel free functioning filter blocking alarm, high or low temperature alarm, low battery alarm, door open alarm and system failure alarm.
- > Made up of stainless steel body with 100-155mm foaming insulation
- > CFC free Danfoss compressor with German EBM fan electromotor
- > Refrigerant used is a mixture of R134a, R404a, R23, R410A, N2
- > Two compressors are used compressors in parallel connection to reduce noise and improve the cooling temperature
- Inner door with double silicon gasket seal prevents loss of cold air with three adjustable stainless steel shelves
- > With 72 hours battery backup for printer and controller display
- > Optional: chart recorder, CO2 back up, storage racks/boxes, remote alarm system

Applications

The -65°C ultra low temperature upright freezers are suitable to be used for medical, clinical, food industries, sanitation, blood banks, and research laboratories.

-65°C Ultra Low Temperature Upright Freezers

Specifications

| Model | LUF-C20 | LUF-C21 | LUF-C22 | | |
|---------------------------------|-----------------------------|--------------|--------------|--|--|
| Capacity | 100L | 218L | 388L | | |
| External Dimension (W×D×H)mm | 720×793×1000 | 940×840×1552 | 940×840×1899 | | |
| Internal Dimension (W×D×H)mm | 450×450×500 | 582×470×768 | 740×450×1200 | | |
| Power Supply | 220V/50Hz | | | | |
| Input Power | 800W | 1000W | 1800W | | |
| Weight (Nt/Gt in Kg) | eight (Nt/Gt in Kg) 120/140 | | 330/360 | | |

| Model | LUF-C23 | LUF-C24 | LUF-C25 | LUF-C26 |
|------------------------------------|--------------|---------------|---------------|---------------|
| Capacity | 538L | 668L | 768L | 828L |
| External Dimension (W×D×H)mm | 940×840×1899 | 996×1075×1897 | 996×1180×1897 | 996×1230×2056 |
| Internal Dimension (W×D×H)mm | 662×600×1330 | 815×667×1200 | 930×665×1200 | 930×710×1308 |
| Power Supply | 220V/50Hz | 220V/50Hz | 220V/50Hz | 220V/50Hz |
| Input Power | 2000W | 2700W | 2700W | 3200W |
| Weight (Nt/Gt in Kg) | 360/380 | 400/420 | 420/450 | 430/460 |



Labodam Equipment Ltd

18a Melton Road Leicester LE4 5EA
United Kingdom
www.labodam.com // info@labodam.com