



CYLINDRICAL WATER BATH LD-LCWB-A10

Cylindrical water bath LD-LCWB-A10 is microprocessor controlled water bath with digital readout, providing precise and constant temperatures within a range of RT to 200°C. They can operate in programmed mode via a digital timer to work in specific time periods, up to 999 min. Equipped with a digital display for visual monitoring of the parameters and timing function for optimization of operating schedules. Inner stainless steel chamber is easy to clean and benefits chemical and corrosion resistance.

Features

- Temperature range is up to 200 °C
- Chamber volume of 6 L
- Digital display for visual monitoring of parameters
- Timing function for optimization of duration
- Non-slip rubber feet ensuring ground stability
- Stainless steel chamber ensuring corrosion resistance

Applications

Used to incubate samples in water, warming reagents, sample thawing, bacteriological examinations, microbiological assays, cell cultivation, waste water laboratories and clinical laboratories.

Specifications

Model No.	LD-LCWB-A10
Capacity	6 L
Temperature Control Range	RT to 200 °C
Ambient Temperature	5 to 40 °C
Time Range	0-999 min
Controller Type	Digital
Internal Dimension (W x H)	260 x 120 mm
External Dimension (W x D x H)	400 x 300 x 220 mm
Power Supply	220 V ; 50 Hz