

Pharmacy Refrigerator LPRF-A30



Pharmacy Refrigerator LPRF-A30

Pharmacy Refrigerator LPRF-A30 is a digital microprocessor controlled unit with user-friendly digital control panel which can store data up to 30 days. It is designed with 580 L holding capacity, 3 to 23°C temperature range, double glass observation door, and 5 pieces wired storage shelves. The cooling and insulation system of this refrigerator is free of CFC gas. Features CR-Ni 304 inner chamber coating, and outer surface made up of galvanized steel, is coated with rust-proof electrostatic paint. It finds application in storage of medical, pharmaceuticals, laboratory products, reagents etc. across different research labs, plants and others.

Features

- LED Light source for Inner chamber lightning
- Fan cooling system to provide equal temperature distribution
- Double thermal gazing door with magnetic seal ring
- Inbuilt full automatic defrost system with digital thermometer thermostat
- Built-in thermal printer is used to print and record the test data
- Audio and visual signal alarm for door open, lower and upper temperature limits exceeding, electricity cut-off, low voltage supply
- Control panel and thermal printer efficiently works up to 24 hours when there is electricity cut-off
- USB output to transfer the data to PC and other external devices in excel format
- Noiseless and user friendly operation mode
- It is in accordance with ISO/CE certificates

Applications

Widely used for storage of products like reagents, raw materials, drugs, finished or in process products, surgical aids, biological samples etc. across pharmacy, life science, medicine, chemistry laboratories, research institute, plants.

Specifications

Model No.	LPRF-A30
Temperature Range	3 °C to 23 °C
Temperature Set Point	+ 4 °C
Number of Wire shelves	5
Net volume	580 L
Gross Volume	638 L
Inner Surface Material	CR-Ni 304
Output	USB
Casters	2 Braked/ 2 Regular
Voltage Supply	195 V to 230 V, 50 Hz
Internal Dimensions (W × L × H)	660 × 712 × 1347 mm
External Dimensions (W × L × H)	765 × 820 × 2000 mm
Weight	215 kg