



***SEMI-AUTOMATIC  
COAGULATION ANALYZER  
LD-LCAZ-A10***

Semi-Automatic Coagulation Analyzer LD-LCAZ-A10 is a compact and portable unit comprehended with scatter turbidimetric assay methodology and 4 constant temperature test channels. Features zero tracking function with optical method detector without visible light interference and magnetic bead. Designed with advanced program self-test and user-friendly interface with LED display, provides quality control analysis function with reaction curve real time monitoring, and ensures reliability of test results. With built-in mixer for easy operation, built-in printer with RS-232 serial port, it offers memory storage for up to 100000 pieces of data with analysis report in international standard format.

### Features:

- ⇒ Compact and portable unit comprehended with scatter turbidimetric assay methodology
- ⇒ 4 constant temperature test channels to perform same or different tests at a time
- ⇒ Zero tracking function, to prevent interference of different sample/reagent
- ⇒ Optical method detector without visible light interference and magnetic bead
- ⇒ Advanced program self-test with user-friendly interface and LED display
- ⇒ Quality control analysis function with reaction curve real time monitoring
- ⇒ Built-in mixer for easy operation and user convenience
- ⇒ Built-in printer with RS-232 serial port for easy printing experience
- ⇒ Large memory storage for up to 100000 pieces of data
- ⇒ Analysis report in international standard format
- ⇒ Highly efficient, stable and reliable with easy operation and good performance

### Applications:

Semi-Automatic Coagulation Analyzer is used to measure a coagulation pathway speed, as well as thrombin and thromboplastin levels, and for detection of blood coagulation factor in medical care, scientific research and education institutions etc.

### Specifications:

Model No.	LD-LCAZ-A10
Method	Scatter turbidimetric assay
Test channels	4 (constant temperature)

Test speed	70 to 110 tests/ hour
Sample preheating position	5
Reagent preheating position	15
Reagent cooling position	3
Preheating time range	1 to 5 mins
Preheating time	30 mins (after start up)
Constant temperature	Test Position: $37^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$ , Preheating Position: $37^{\circ}\text{C} \pm 1^{\circ}\text{C}$ , Cooling Position: $\leq 12^{\circ}\text{C}$
Test items	Prothrombin time (PT), activated partial thromboplastin time (APTT), thrombin time (TT), fibrinogen (FIB), coagulation factors II-XII, etc.
Accuracy	PT: $\text{CV} \leq 2.5\%$ , APTT: $\text{CV} \leq 3\%$ , TT: $\text{CV} \leq 3\%$ , FIB: $\text{CV} \leq 5\%$
Channel difference	PT tests in different channels: $\leq 10\%$
Test accuracy	FIB relative bias $\leq \pm 10.0\%$
Linearity	FIB linearity $r \geq 0.975$
Reagent volume	PT : 200 $\mu\text{l}$ , APTT : 100 $\mu\text{l}$ , TT : 100 $\mu\text{l}$ , FIB : 100 $\mu\text{l}$
Sample volume	PT; APTT; TT: 100 $\mu\text{l}$ , FIB: 200 $\mu\text{l}$
Display	LED: 128 $\times$ 64 mm
Printer	Built-in
Interface	RS-232

Storage	Up to 100000 pieces of data
Power supply	AC 220 ± 22 V 50 ± 1 Hz
Power	≤ 85 VA
Packaging dimension (W×D×H)	510 × 480 × 220 mm
Net weight	9 kg
Gross weight	11 kg