

Stainless Steel Water Distiller

LSWD-A1 series



www.labodam.com info@labodam.com

Stainless Steel Water Distiller LSWD-A1 series

Stainless Steel Water distiller LSWD-A1 series are electrical floor mounted single reservoir distillation units. Stainless steel construction aids to produce germ-free distillate. Narrow piping connects heater column to heat exchanger for optimal distillate quality. Exhaust vent provides an outlet for odour or gases to be released without causing contamination.

Features

- > USP grade pyrogen-free distillate
- > Shunt valve regulates inlet and outlet flow
- Gas/stench exhaustion vent
- Corrosion-proof reservoir

Application

Used in laboratory, organic chemistry lab, fermentation and medical industry to produce industrial grade highly treated and distilled water suitable for laboratory usage.

Specification

MODEL NO	LSWD-A10	LSWD-A11	LSWD-A12
Capacity	5 L/hr	10 L/hr	20 L/hr
Water consumption	1:10	1:10	1:10
Configuration	Standard control	Standard control	Standard control
Water type	Regular water	Regular water	Regular water
Power	220 V ; 2.5 kW	380 V; 2.5 kW	380 V;4.5 kW
	Single phase	Triplephase	Triplephase
Dimensions	365 × 368 × 845 mm	365 × 368 × 845 mm	365 × 368 ×945 mm
Weight	9 kgs	9 kgs	10kgs