

**STAINLESS STEEL  
WATER BATH  
LD-LSBC-A12**



Stainless Steel Water Bath LD-LSBC-A12 is a microprocessor controlled water bath with chamber volume capacity of 30 L, providing precise and constant temperatures within a range of RT (5 °C ~ 99 °C). Equipped with a digital display for visual monitoring of the parameters and timing function for optimization of operating schedules. Features audible and visual alarm for over and under temperature, protecting samples at set temperature. Inner and outer stainless steel chamber is easy to clean and benefits chemical and corrosion resistance.

## Features

- ✚ Temperature range is RT (+5 °C ~ 99 °C)
- ✚ Chamber volume capacity - 30 L
- ✚ Digital display for visual monitoring of parameters
- ✚ Timing function for optimization of duration
- ✚ Audio-visual alarm for over temperature protection
- ✚ Non-slip rubber feet ensuring ground stability
- ✚ Stainless steel chamber ensuring corrosion resistance

## Applications

Used to incubate samples in water, warming reagents, sample thawing, bacteriological examinations, microbiological assays, cell cultivation, waste water laboratories and clinical laboratories.

## Specifications

Model No.	LD-LSBC-A12
Chamber Volume	30 L
Temperature Range	RT (+ 5 °C ~ 99 °C)
Temperature Stability	±0.5 °C
Timing Range	1 ~ 999 min
Controller Type	Digital
Power Consumption	1000 W
Power Supply	220 V ; 50 Hz
Internal Dimension (W x D x H)	600 x 300 x 160 mm
External Dimension (W x D x H)	760 x 340 x 190 mm
Packing Dimension (W x D x H)	850 x 430 x 390 mm
Net Weight	13 kg
Gross Weight	18 kg