



TABLE TOP AUTOCLAVE

LTTA-B1 SERIES

Table top Autoclave LTTA-BI Series

Table top autoclave LTTA-BI series is robust and compact, space efficient unit with a sterilizing temperature of 134 °C. It is equipped with auto dry function along with safety features like automatic shutoff preventing overheating of chamber, automatic cold air discharge and auto protection against raised temperature and pressure making a reliable and user friendly device. Qualitative results are achieved due to automation avoiding human errors.

Features

- Digital LCD display to monitor working status and parameters
- Working temperature : 134 °C
- 4 - 6 mins rapid sterilization
- Automated drying function
- Equipped with interior circulate system
- Inner steam circulatory system
- Automatic cold air discharge from system chamber ensures dry and clean environment
- Door lock feature : Door cannot be opened till the pressure inside the chamber doesn't fall to 0.027 MPa
- Self-inflating leak proof chamber
- Auto exhaustion of cool air
- Safe door lock system ensuring safety / protection during sterilization
- Automatic power cut off with alarm with low water levels indication
- Stainless steel sterilizing trays

Application

Used to sterilize culture media, instruments, dressings, intravenous equipments, rubber closure of glass equipments used in aseptic techniques and numerous objects that can withstand high temperature and pressure

Specification

Model	LTTA-B10	LTTA-B11	LTTA-B12	LTTA-B13
Capacity	20 L	24 L	35 L	50 L
Number of sterilizing trays	3	3	4	4
Sterilization Temperature	105 °C-134 °C			
Sterilization Pressure	0.22 MPa			
Timer Range	0-99 minutes			
Chamber Dimension (Φ×D)	250×420 mm	250×520 mm	300×500 mm	340×550 mm
Net Weight	40 Kgs	45 Kgs	78 Kgs	93 Kgs
Gross Weight	43 Kgs	50 Kgs	95 Kgs	112 Kgs
Power Supply	1.5 KW / AC220V 50 Hz		2.7 KW/AC 220V 50 Hz	