



PRP Centrifuge LD-LPRP-A11

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

PRP Centrifuge LD-LPRP-A11

Overview

Refrigerated PRP Centrifuge LD-LPRP-A11 is engineered for efficient separation of platelet-rich plasma (PRP), fat, and other biological samples. Designed for precision, safety, and dependable performance, it is suitable for clinical and laboratory workflows requiring controlled centrifugation and temperature regulation. The unit supports a variety of PRP kits and tube configurations, making it a versatile solution for regenerative medicine and laboratory applications.

Features:

- Microprocessor-controlled system with frequency-conversion brushless AC motor for reliable operation
- LCD display enables intuitive parameter setting and real-time monitoring
- Imbalance detection, over speed protection, and lid-lock safety system ensure secure operation
- Adjustable speed, time, acceleration, and deceleration settings for process flexibility
- Free-time braking function improves sample handling efficiency
- Compatible with multiple PRP kits, tubes, and syringe rotors for enhanced versatility
- Sealed syringe cover, plugs, and adapters minimize contamination during fat-transfer procedures
- Optimized rotor design delivers high PRP recovery with improved separation efficiency

Applications:

Ideal for platelet-rich plasma (PRP) preparation, fat purification, regenerative medicine, cosmetic surgery, dermatology centres, blood processing laboratories, and biomedical research facilities. It is also suitable for applications involving cell separation and sample preparation.

Specifications:

Motor	Microprocessor Control, Frequency Conversion Motor
Display	LCD
Rotor 1	Swing Rotor, 4 × 60 mL
Rotor 2	Swing Rotor, 16 × 15 mL
Rotor 3	Syringe Rotor, 4 × 20/50 mL
Rotor 4	Custom Rotor (Optional)
Net Weight	80 kg
Maximum RCF	4390 × g
Noise Level	≤60 dB(A)
Timer Range	0–99 min

Power Supply	AC 110/220 V, 50/60 Hz, 5 A
Maximum Speed	5000 rpm
Speed Accuracy	±20 rpm
Temperature Range	-20°C to +40°C
Dimensions (L × W × H)	620 × 690 × 415 mm