



Walk-in Fumehood LD-LWF-A11

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Walk-in Fumehood LD-LWF-A11

Overview

Walk-In Fumehood LWF-A11 has a large opening and is mounted on the floor. It is ideal in situations that require large materials to be walked or loaded in. It can be opened to a maximum height of 1300 mm. Meets the standard of a low velocity high performance hood. Consists of large room exhaust system and option of filter installation which minimizes environmental pollution.

Features:

- 2 unit of LED lamp: 12 W ~ 16 W
- Memory function in case of power failure
- Operators can walk into the fumehood
- Large room exhaust system
- Option of filter installation which minimizes environmental pollution
- Manual toughened front glass window
- Exterior material made up of 1.0 mm cold-rolled steel
- Interior made up of excellent quality melamine board resistant to acid and base

Applications:

Walk-in Fumehood find applications in pharmaceutical, educational, hospital, healthcare and manufacturing laboratories.

Specifications:

Noise	62 dB
LED Lamp	16 W × 2
Vibration	XYZ direct ? 4 µm
Illumination	? 800 Lux
Maximum Opening	1300 mm
Power Consumption	600 W
Exhaust Blower Size	970 × 810 × 720 mm
Inflow Air Velocity	0.3 m/s to 0.8 m/s
Exhaust Airflow Volume	1500 m ³ /h
Package Size (W × D × H)	1710 × 1050 × 2430 mm
Exterior Size (W × D × H)	1500 × 800 × 2200 mm
Interior Size (W × D × H)	1280 × 600 × 1650 mm