



Dispensing peristaltic pump LD-LDPP-A11

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Dispensing peristaltic pump LD-LDPP-A11

Overview

Dispensing peristaltic pump LDPP-A11 is equipped with a touch screen controller that allows monitoring of parameters and change of speed. Equipped with a flow rate of 0.006 to 1600 mL/min and 0.006 ~ 2900 mL/min and advanced features such as flow rate calibration and anti-drip function. Four operational modes available for easy functioning. Intelligent cooling fan control helps in minimizing the work noise

Features:

- Operational modes : Volume Dispense, Time Dispense, Copy Dispense and Flow Mode
- LCD display for monitoring parameters
- Anti-drip function ensuring dispense accuracy
- Speed resolution : 0.1 rpm
- Adjustable rotating speed
- Intelligent temperature control minimizing working noise
- Reversible operation allowing pumping in both directions
- Multi channels with interchangeable pump heads for varied applications
- Easy liquid auto dispensation by time or volume
- Internal double layer isolation
- Dust and moisture proof circuit board
- Optional remote infrared control
- Robust and protected with ABS plastic housing
- Low noise operation

Specifications:

Weight	5.5 kg
IP grade	IP 31
Flow Range	0.006 ~ 2900 mL/min
Speed Range	0.1 ~ 600 rpm
Power supply	AC 220 V $\pm$ 10 % , 50 Hz / 60 Hz
Flow Accuracy	0.002
No of channel	1
Speed Resolution	0.1 rpm
Power Consumption	< 50 W
Relative Humidity	< 80 %
Ambient Temperature	0 ~ 40 °C
Dimensions (L x W x H)	257 x 182 x 198 mm