



Intelligent flow peristaltic pump LD-LIFP-C11

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Intelligent flow peristaltic pump LD-LIFP-C11

Overview

Intelligent flow peristaltic pump LIFP-C11 is equipped with a touch screen controller that allows monitoring of parameters and change of speed. Equipped with advanced features such as flow rate calibration and anti-drip function. Easy dispense mode to dispense the recorded volume by one touch DISPENSE key. Intelligent cooling fan control helps in minimizing the work noise

Features:

- LCD display for monitoring parameters
- Anti-drip function ensuring dispense accuracy
- Speed resolution : 0.1 rpm
- Adjustable rotating speed
- Intelligent temperature control minimizing working noise
- Reversible operation allowing pumping in both directions
- Multi channels with interchangeable pump heads for varied applications
- Easy liquid auto dispensation by time or volume
- Internal double layer isolation
- Dust and moisture proof circuit board
- Optional remote infrared control
- Robust and protected with ABS plastic housing
- Low noise operation

Specifications:

Weight	4.8 kg
IP grade	IP 31
Flow Range	0.00011 ~ 720 mL/min
Speed Range	0.1 ~ 150 rpm
Power supply	AC 220 V $\pm$ 10 % , 50 Hz / 60 Hz
Flow Accuracy	0.2 %.
No of channel	4
Speed Resolution	0.1 rpm
Power Consumption	< 30 W
Relative Humidity	< 80 %
Ambient Temperature	0 ~ 40 °C
Dimensions (L x W x H)	257 x 198 x 182 mm