



Variable speed peristaltic pump LD-LVSP-B10

Labodam Equipment Ltd.

info@labodam.com | www.labodam.com

Variable speed peristaltic pump LD-LVSP-B10

Overview

Variable speed peristaltic pump LVSP-B10 is a dual channelled precise dispensing peristaltic pumps to meet laboratory liquid handling needs. Equipped with varied flow range and speed accuracy it allows reversible operation to pump in both directions. Provides high levels of volumetric accuracy without contaminating the fluid during the operation. Interchangeable pump heads help in delivering smooth and low pulse flows.

Features:

- Digital speed indication
- Autosave™s running parameters on power or system failure
- Reversible operation allowing pumping in both directions
- Easy liquid auto dispensation by time or volume
- Multi channels with interchangeable pump heads for varied applications
- Dust and moisture proof circuit board
- Adjustable rotating speed
- Robust and protected with ABS plastic housing
- Low noise operation

Specifications:

Weight	2.7 kg
IP grade	IP 31
Flow Range	0.00011 - 190 mL / min
Speed Range	0.1 ~ 50 rpm
Power supply	AC 220 V $\pm$ 10 % , 50 Hz / 60 Hz
Flow Accuracy	0.5 %.
No of channel	2
Power Consumption	< 25 W
Relative Humidity	< 80 %
Ambient Temperature	0 ~ 40 °C
Dimensions (L x W x H)	225 x 132 x 128 mm