



Integrated Industrial Ultrasonic Cleaner LD- LIUC-A16

Labodam Equipment Ltd.
info@labodam.com | www.labodam.com

Integrated Industrial Ultrasonic Cleaner LD-LIUC-A16

Overview

Integrated Industrial Ultrasonic Cleaner LIUC-A16 is a 264 L capacited unit integrated with industrial based transducer and a powerful ultrasonic generator providing efficient high level tabletop cleaning. With a cleaning duration of 1 ~ 99 mins efficient intensive cleaning of instruments and products is done making them contamination, rust and germ free. Its key feature is the variance of using it at 28 KHz for gross rinse to 40 KHz for intensive rinse.

Features:

- 264 L capacity tank
- Temperature range : 0 °C ~ 80 °C
- Cleaning duration : 1 ~ 99 mins
- 28 KHz for gross rinse to 40 KHz for intensive rinse
- Inbuilt with industrial based transducer and powerful ultrasonic generator
- One key access for auto stand-by , sleep and wake up mode
- Integrated digital circuit for timer and heater
- Precise digital processed temperature controls
- Optimum durability under prolonged and heavy usage
- Equipped with degassing and degreasing function

Applications:

Used in cleaning of irregular and complex specialized instruments, components of sundry shops, workshops, factories etc.

Specifications:

Timer	1 ~ 99 mins
Voltage	AC 220 V / 50 Hz
Capacity	264 L
Drainage	Yes
Heater power	6000 W
Temperature set	0 °C ~ 80 °C
Ultrasonic power	1500 ~ 3000 W
Construction material	Stainless Steel
Tank size (L x W x H)	800 x 600 x 550 mm
Overall size (L x W x H)	1070 x 780 x 1010 mm